XCMG BRIEFING

Founded in 1943 as Huaxing Factory, XCMG is a pioneer, founder, and leader in China's construction machinery industry. Today, it has grown into a globally competitive and influential enterprise with a market value exceeding RMB 100 billion and a world-leading brand. XCMG consistently ranks No.1 in China's construction machinery industry and is the only Chinese manufacturer to remain among the global top four for six consecutive years. The company has also been listed among the World's 500 Most Influential Brands for seven consecutive years and is included in both the Fortune China 500 and Forbes China's Top 30 Go-International Brands. Today, XCMG has developed one of the most comprehensive product portfolios in the global construction machinery industry, with business spanning 14 major industrial sectors, 95 product categories, and 218 product lines. To drive continuous innovation, XCMG has established six major R&D centers in China, the United States, Germany, Brazil, Australia, and South Asia, forming a coordinated and highly efficient global R&D network. In manufacturing, XCMG operates more than ten production bases and KD plants across China, Germany, Austria, the United States, Mexico, and Uzbekistan. Through the acquisition of international brands such as Schwing and WIKA, XCMG continues to strengthen its capabilities in key technologies and core components. Today, XCMG has built a global marketing and service network across 14 global regions, with more than 300 overseas distributors and over 2,000 service sites. Its products are exported to 195 countries and regions, with coverage exceeding 95% of Belt and Road markets worldwide, making XCMG a flagship brand representing China's equipment manufacturing industry on the global stage.

SOLID TO SUCCEED



Oceania
Pilbara Iron Ore Project, Australia


South America
El Mirador copper mine, Ecuador


Africa
Dangote Refinery Project, Nigeria


MENA
Duqm Oil Refinery, Oman


Africa
Simandou Iron Ore Project, Guinea


Europe
Ivovik Wind Farm Project, Bosnia and Herzegovina


South America
Bahia Wind Farm Project, Brazil

HEAVY-DUTY TRUCK

● SPECIAL OPERATION VEHICLE (INTEGRATED CHASSIS)


XGA3252D9WCX
Drive Type:6×4
Wheel Base: 3200+1350mm
Kerb Mass: 7800kg
GCW: 25000kg
Max.Speed: 89km/h
Fuel Tank: 350L


XGA3252BEVWEX
Drive Type:6×4
Wheel Base: 3450+1350mm
Kerb Mass: 8000kg
GCW: 25000kg
Max.Speed: 89km/h
Fuel Tank: 350L


XGA3251D2WCLX
(XMA9M81)
Drive Type:6×4
Wheel Base: 4050+1400mm
Kerb Mass: 10380kg
GCW: 31000kg
Max.Speed: 89km/h
Fuel Tank: 400L


XGA3251D2WCLX
(XMA9M81)
Drive Type:6×4
Wheel Base: 4050+1400mm
Kerb Mass: 10380kg
GCW: 31000kg
Max.Speed: 89km/h
Fuel Tank: 400L


XGA3310D5WEX
(XMA9M81)
Drive Type:6×4
Wheel Base: 1950+1350+1350mm
Kerb Mass: 11230kg
GCW: 33000kg
Max.Speed: 89km/h
Fuel Tank: 400L


XGA3251D5WCX
(XMA9M81)
Drive Type:6×4
Wheel Base: 4000+1400mm
Kerb Mass: 10450kg
GCW: 31000kg
Max.Speed: 89km/h
Fuel Tank: 400L


XGA3252D6WCX
Drive Type:6×4
Wheel Base: 4000+1400mm
Kerb Mass: 10450kg
GCW: 31000kg
Max.Speed: 89km/h
Fuel Tank: 400L


XGA3251D5WCX
Drive Type:6×4
Wheel Base: 4000+1400mm
Kerb Mass: 10450kg
GCW: 31000kg
Max.Speed: 89km/h
Fuel Tank: 400L


XT4018K
Maximum lifting capacity: 400t
Operation height: 77.22m
Operation radius: 34.5m
Lifting capacity at maximum height: 2000kg
Lifting capacity at maximum radius: 850kg
Maximum speed: 25km/h


XT4018KH
Maximum lifting capacity: 400t
Operation height: 77.22m
Operation radius: 34.5m
Lifting capacity at maximum height: 2000kg
Lifting capacity at maximum radius: 850kg
Maximum speed: 25km/h


XT4018BKH
Maximum lifting capacity: 400t
Operation height: 77.22m
Operation radius: 34.5m
Lifting capacity at maximum height: 2000kg
Lifting capacity at maximum radius: 850kg
Maximum speed: 25km/h


XT4018KH
Maximum lifting capacity: 400t
Operation height: 77.22m
Operation radius: 34.5m
Lifting capacity at maximum height: 2000kg
Lifting capacity at maximum radius: 850kg
Maximum speed: 25km/h


XT3207K
Maximum lifting capacity: 320t
Operation height: 72m
Lifting capacity at maximum height: 3200kg
Operation radius: 42m
Lifting capacity at maximum radius: 1400kg
Maximum speed: 40km/h


XT3207KH
Maximum lifting capacity: 320t
Operation height: 77.7m
Lifting capacity at maximum height: 3200kg
Operation radius: 42m
Lifting capacity at maximum radius: 1200kg
Maximum speed: 40km/h


XT3514K
Maximum lifting capacity: 350t
Operation height: 72.3m
Lifting capacity at maximum height: 3500kg
Operation radius: 42m
Lifting capacity at maximum radius: 1400kg
Maximum speed: 25km/h


XT4014K
Maximum lifting capacity: 400t
Operation height: 72.83m
Lifting capacity at maximum height: 3000kg
Operation radius: 42m
Lifting capacity at maximum radius: 1500kg
Maximum speed: 27km/h


XT4014KH
Maximum lifting capacity: 400t
Operation height: 73.37m
Lifting capacity at maximum height: 3000kg
Operation radius: 42m
Lifting capacity at maximum radius: 1500kg
Maximum speed: 27km/h


XT8010K
Maximum lifting capacity: 800t
Operation height: 81.5m
Lifting capacity at maximum height: 4500kg
Operation radius: 52m
Lifting capacity at maximum radius: 2000kg
Maximum speed: 25km/h


XT12010K
Maximum lifting capacity: 1200t
Operation height: 81.5m
Lifting capacity at maximum height: 7000kg
Operation radius: 52m
Lifting capacity at maximum radius: 3000kg
Maximum speed: 25km/h


XT4518KH
Maximum lifting capacity: 450t
Operation height: 77.22m
Operation radius: 34.5m
Lifting capacity at maximum height: 2000kg
Lifting capacity at maximum radius: 850kg
Maximum speed: 25km/h


XT4518BKH
Maximum lifting capacity: 450t
Operation height: 77.22m
Operation radius: 34.5m
Lifting capacity at maximum height: 2000kg
Lifting capacity at maximum radius: 850kg
Maximum speed: 25km/h


XT4514K
Maximum lifting capacity: 450t
Operation height: 77.22m
Operation radius: 34.5m
Lifting capacity at maximum height: 2940kg
Operation radius: 52m
Lifting capacity at maximum radius: 1400kg
Maximum speed: 25km/h


XT5017K
Maximum lifting capacity: 500t
Operation height: 77.7m
Lifting capacity at maximum height: 2267kg
Operation radius: 52.5m
Lifting capacity at maximum radius: 1360kg
Maximum speed: 32km/h


XT5517K
Maximum lifting capacity: 550t
Operation height: 77.7m
Lifting capacity at maximum height: 2267kg
Operation radius: 52.5m
Lifting capacity at maximum radius: 1360kg
Maximum speed: 32km/h


XT6517K
Maximum lifting capacity: 540kg
Operation height: 77.7m
Lifting capacity at maximum height: 2267kg
Operation radius: 52.5m
Lifting capacity at maximum radius: 1357kg
Maximum speed: 32km/h


XT8010K
Maximum lifting capacity: 800t
Operation height: 81.5m
Lifting capacity at maximum height: 4500kg
Operation radius: 52m
Lifting capacity at maximum radius: 2000kg
Maximum speed: 25km/h


XT12010K
Maximum lifting capacity: 1200t
Operation height: 81.5m
Lifting capacity at maximum height: 7000kg
Operation radius: 52m
Lifting capacity at maximum radius: 3000kg
Maximum speed: 25km/h


XT19010K
Maximum lifting capacity: 1900t
Operation height: 81.5m
Lifting capacity at maximum height: 11035kg
Operation radius: 52m
Lifting capacity at maximum radius: 4500kg
Maximum speed: 25km/h


XT23010K
Maximum lifting capacity: 2300t
Operation height: 82.5m
Lifting capacity at maximum height: 10000kg
Operation radius: 52m
Lifting capacity at maximum radius: 6440kg
Maximum speed: 25km/h

● SEMI-TRAILER TRACTOR


XGA5251J9QW2
(Complete Vehicle)
Drive Type:6×4
Wheel Base: 3200+1350mm
Kerb Mass: 10000kg
GCW: 35000kg
Max.Speed: 89km/h
Fuel Tank: 400L


XGA4253BEVWC
Drive Type:6×4
Wheel Base: 3200+1350mm
Kerb Mass: 11400kg
GCW: 35000kg
Max.Speed: 89km/h
Battery power: 352.8kWh


XGA4254BEVWC
Drive Type:6×4
Wheel Base: 3200+1350mm
Kerb Mass: 11700kg
GCW: 35000kg
Max.Speed: 89km/h
Battery power: 403.68kWh


XGA4256BEVWC
Drive Type:6×4
Wheel Base: 3200+1350mm
Kerb Mass: 12700kg
GCW: 35000kg
Max.Speed: 89km/h
Battery power: 604.8kWh

XGA4252D2WC
(XMA9M81)
Drive Type:6×4
Wheel Base: 3200+1350mm
Kerb Mass: 10780kg
GCW: 35000kg
Max.Speed: 89km/h
Fuel Tank: 400L

HOISTING MACHINERY

● TRUCK CRANE

XCT15L4_Y
Max.Total Rated Lifting Load: 15t
Max.Load Moment of Base Boom: 180t•m
Max.Boom Length: 32.2m
Dead Weight in Travel Status: 44t

XCT20L5
Max.Total Rated Lifting Load: 20t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT25L4_Y
Max.Total Rated Lifting Load: 25t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT25L5_Y
Max.Total Rated Lifting Load: 25t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT25L5_S
Max.Total Rated Lifting Load: 25t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT25L5_SR
Max.Total Rated Lifting Load: 25t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT25L5_SL
Max.Total Rated Lifting Load: 25t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT25L5_LY
Max.Total Rated Lifting Load: 25t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT25L5_LR
Max.Total Rated Lifting Load: 25t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT25L5_LL
Max.Total Rated Lifting Load: 25t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT25L5_LY
Max.Total Rated Lifting Load: 25t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT25L5_LR
Max.Total Rated Lifting Load: 25t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT25L5_LL
Max.Total Rated Lifting Load: 25t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT25L5_Y
Max.Total Rated Lifting Load: 25t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT25L4_S1
Max.Total Rated Lifting Load: 25t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT25L4_SR
Max.Total Rated Lifting Load: 25t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT25L4_SL
Max.Total Rated Lifting Load: 25t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT25L4_LY
Max.Total Rated Lifting Load: 25t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT25L4_LR
Max.Total Rated Lifting Load: 25t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT25L4_LL
Max.Total Rated Lifting Load: 25t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT25L4_Y
Max.Total Rated Lifting Load: 25t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT35L4_Y1
Max.Total Rated Lifting Load: 35t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT35L_Y
Max.Total Rated Lifting Load: 35t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT40L_BR
Max.Total Rated Lifting Load: 40t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT40L_LY
Max.Total Rated Lifting Load: 40t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT50L_BR
Max.Total Rated Lifting Load: 50t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT50L_LY
Max.Total Rated Lifting Load: 50t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT70L_BR
Max.Total Rated Lifting Load: 70t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT70L_LY
Max.Total Rated Lifting Load: 70t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT70L_LR
Max.Total Rated Lifting Load: 70t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT70L_LL
Max.Total Rated Lifting Load: 70t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT70L_Y
Max.Total Rated Lifting Load: 70t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT90L_BR
Max.Total Rated Lifting Load: 90t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT90L_LY
Max.Total Rated Lifting Load: 90t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT90L_LR
Max.Total Rated Lifting Load: 90t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT90L_LL
Max.Total Rated Lifting Load: 90t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT90L_Y1
Max.Total Rated Lifting Load: 90t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT90L_Y
Max.Total Rated Lifting Load: 90t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT90XL_Y
Max.Total Rated Lifting Load: 90t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT90XL_LY
Max.Total Rated Lifting Load: 90t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT90XL_LR
Max.Total Rated Lifting Load: 90t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT90XL_LL
Max.Total Rated Lifting Load: 90t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT90XL_Y
Max.Total Rated Lifting Load: 90t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT90XL_H
Max.Total Rated Lifting Load: 90t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT90XL_HY
Max.Total Rated Lifting Load: 90t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT90XL_HR
Max.Total Rated Lifting Load: 90t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT90XL_HL
Max.Total Rated Lifting Load: 90t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT90XL_HH
Max.Total Rated Lifting Load: 90t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT90XL_HH
Max.Total Rated Lifting Load: 90t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT90XL_HY
Max.Total Rated Lifting Load: 90t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT90XL_HR
Max.Total Rated Lifting Load: 90t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT90XL_HL
Max.Total Rated Lifting Load: 90t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT90XL_HH
Max.Total Rated Lifting Load: 90t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT100L_S
Max.Total Rated Lifting Load: 100t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT100L_SR
Max.Total Rated Lifting Load: 100t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT100L_SL
Max.Total Rated Lifting Load: 100t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT100L_LY
Max.Total Rated Lifting Load: 100t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT110H
Max.Total Rated Lifting Load: 110t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT115L_Y
Max.Total Rated Lifting Load: 115t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT115L_Y(280V)
Max.Total Rated Lifting Load: 115t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT120DRI
Max.Total Rated Lifting Load: 120t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT130L_Y
Max.Total Rated Lifting Load: 130t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT130DT-1H
Max.Total Rated Lifting Load: 130t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT130DT-1Y
Max.Total Rated Lifting Load: 130t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT130DT-1HR
Max.Total Rated Lifting Load: 130t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT130DT-1YR
Max.Total Rated Lifting Load: 130t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT130DT-1HL
Max.Total Rated Lifting Load: 130t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT130DT-1YL
Max.Total Rated Lifting Load: 130t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT160L_Y(280V)
Max.Total Rated Lifting Load: 160t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT200RI
Max.Total Rated Lifting Load: 200t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT200L_S
Max.Total Rated Lifting Load: 200t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT200L_SR
Max.Total Rated Lifting Load: 200t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT200L_SL
Max.Total Rated Lifting Load: 200t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT200L_LY
Max.Total Rated Lifting Load: 200t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT200L_LR
Max.Total Rated Lifting Load: 200t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT200L_LL
Max.Total Rated Lifting Load: 200t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT200L_Y
Max.Total Rated Lifting Load: 200t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT200L_H
Max.Total Rated Lifting Load: 200t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT200L_HY
Max.Total Rated Lifting Load: 200t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT200L_HR
Max.Total Rated Lifting Load: 200t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT200L_HL
Max.Total Rated Lifting Load: 200t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT200L_HH
Max.Total Rated Lifting Load: 200t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT200L_HH
Max.Total Rated Lifting Load: 200t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT200L_HY
Max.Total Rated Lifting Load: 200t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT200L_HR
Max.Total Rated Lifting Load: 200t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT200L_HL
Max.Total Rated Lifting Load: 200t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT200L_HH
Max.Total Rated Lifting Load: 200t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT220L
Max.Total Rated Lifting Load: 220t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT220L_H
Max.Total Rated Lifting Load: 220t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT220L_HY
Max.Total Rated Lifting Load: 220t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT220L_HR
Max.Total Rated Lifting Load: 220t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT220L_HL
Max.Total Rated Lifting Load: 220t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT220L_HH
Max.Total Rated Lifting Load: 220t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT250L
Max.Total Rated Lifting Load: 250t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT250L_H
Max.Total Rated Lifting Load: 250t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT250L_HY
Max.Total Rated Lifting Load: 250t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT250L_HR
Max.Total Rated Lifting Load: 250t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT250L_HL
Max.Total Rated Lifting Load: 250t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT250L_HH
Max.Total Rated Lifting Load: 250t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT250L_HH
Max.Total Rated Lifting Load: 250t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT250L_HY
Max.Total Rated Lifting Load: 250t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT250L_HR
Max.Total Rated Lifting Load: 250t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT250L_HL
Max.Total Rated Lifting Load: 250t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT250L_HH
Max.Total Rated Lifting Load: 250t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT400L
Max.Total Rated Lifting Load: 400t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT400L_H
Max.Total Rated Lifting Load: 400t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT400L_HY
Max.Total Rated Lifting Load: 400t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT400L_HR
Max.Total Rated Lifting Load: 400t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT400L_HL
Max.Total Rated Lifting Load: 400t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT400L_HH
Max.Total Rated Lifting Load: 400t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT500L_HH
Max.Total Rated Lifting Load: 500t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT500L_HH
Max.Total Rated Lifting Load: 500t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT700L_HH
Max.Total Rated Lifting Load: 700t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT700L_HH
Max.Total Rated Lifting Load: 700t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT1000L_HH
Max.Total Rated Lifting Load: 1000t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT1000L_HH
Max.Total Rated Lifting Load: 1000t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT1200RI
Max.Total Rated Lifting Load: 1200t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT160L_Y(185kV)
Max.Total Rated Lifting Load: 160t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT1600RI
Max.Total Rated Lifting Load: 1600t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT2000L_HH
Max.Total Rated Lifting Load: 2000t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT2000RI
Max.Total Rated Lifting Load: 2000t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT2500L_HH
Max.Total Rated Lifting Load: 2500t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT2500L_HH
Max.Total Rated Lifting Load: 2500t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT3000L_HH
Max.Total Rated Lifting Load: 3000t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT3000L_HH
Max.Total Rated Lifting Load: 3000t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT4000RI
Max.Total Rated Lifting Load: 4000t
Max.Load Moment of Base Boom: 159t•m
Max.Boom Length: 32m
Dead Weight in Travel Status: 46t

XCT4000L_HH